

## WPTOUCH

### DIGITAL CONTROLS & PANELS

#### *Digital Remote Control*



### PRODUCT OVERVIEW

Digital remote control for MIMO88 and MIMO88SG matrixes.

#### KEY FEATURES

- Digital remote control, compatible with the MIMO88 digital matrix (CAN-BUS)
- 2 touch-sensitive keys
- 1 touch-sensitive jog wheel
- 1 IR receiver
- 2x16 char. LCD transfective display
- Programmable under the MIMO88 / MIMO88SG control (digital mode)
- Compatible with the DAM614 for both volume control and source selection (analogue mode)
- Compatible with other products with 0-10 VDC ports (MPA, ALMA, CA, NXA, etc.) for volume control and/or source selection (using an external power supply)
- Recessed or top-wall mount with included accessory

#### APPLICATIONS

- Remote control, managing source selection / preset selection, volume control and MUTE or other programmable functions (depending on attached devices)

### TECHNICAL DATA

<b>Power DC</b>	10~17V DC
<b>Power consumption</b>	32 mA
<b>Cable length, Analogue mode</b>	Up to 500m, min. wire section of 0.5mm <sup>2</sup> (with WP-PSU power supply).
<b>Cable length, Digital mode</b>	Up to 1000m with CAT5 or better (with WP-PSU power supply).
<b>Dimensions WxDxH</b>	86 x 35 x 86 mm
<b>Weight</b>	65 g.